

Make New OMOTENASHI

HOTCABI Pro model

2 models × 2 types

Simple and Easy!



- Easy control by simple control panel with pictograph. Also easy to see the operating mode with LED light.
- Smooth touch control panel is located upper side that reduces contamination by foreign objects.



Functional! High-spec!

- Chemical resistance plastic reduces chemical attack cracking.
- Great temperature control system and better heat permeability provide additional stability.



Made in **J**apan

SSS **HOT** UV lamp model

- 1 door type HC-11UV Pro
- 2 door type HC-21UV Pro

SSS **HOT** **COOL** HOT & COOL model

- 1 door type HC-11LX Pro
- 2 door type HC-21LX Pro

HOTCABI/COOLCABI

Upgraded cabi for advanced presentation that provides a welcome service and gracious expression of hospitality.

HC-11UV Pro

UV lamp model
1 door type



Sterilizing UV lamp



HC-11LX Pro

HOT & COOL CONVERTIBLE CABI
1 door type



Convertible HOT COOL



HC-21UV Pro

UV lamp model
2 door type



Sterilizing UV lamp



HC-21LX Pro

HOT & COOL CONVERTIBLE CABI
2 door type



Convertible HOT COOL HOT COOL



Model	HC-11UV Pro	HC-21UV Pro	HC-11LX Pro	HC-21LX Pro
Supply voltage	AC110-120V AC220-240V	AC110-120V AC220-240V	- AC220-240V	- AC220-240V
Power consumption	190W	380W	150W	300W
Outer dimensions	W450 x D363 x H322 mm	W450 x D363 x H562 mm	W450 x D363 x H322 mm	W450 x D363 x H562 mm
Inner dimensions	W348 x D207 x H152 mm	W348 x D207 x H152 mm x 2 door	W348 x D207 x H152 mm	W348 x D207 x H152 mm x 2 door
Capacity	11 liters 55 hand towels (approx. 25 face towels)	11 liters x 2 door 110 hand towels (approx. 50 face towels)	11 liters 55 hand towels (approx. 25 face towels)	11 liters x 2 door 110 hand towels (approx. 50 face towels)
Net weight	7.5 kg	11.5 kg	10 kg	17 kg
Tem. control	Electronics control	Electronics control	Electronics control / Peltier device	Electronics control / Peltier device
Cabinet inside temp.	70-80°C (158-176°F)	70-80°C (158-176°F)	HOT : 70-80°C (158-176°F) COOL : 7-10°C (44-50°F)	HOT : 70-80°C (158-176°F) COOL : 7-10°C (44-50°F)
Accessories	Basket x 1, drain tray x 1	Basket x 2, drain tray x 1	Basket x 1, drain tray x 1	Basket x 2, drain tray x 1
Sterilizing lamp	GTL-2 2W x 1	GTL-2 2W x 2	-	-
Safety standard	ETL / cETL / CE	ETL / cETL / CE	CE	CE

● UV lamp does not light up when the door is opened. 2